

FEATURES

- Plastic housing
- Support regular shutdown, random code decryption function
- Auto networking and auto auto-creating weighing scale system
- Power on, auto zero-setting range, manual zero-setting range can be set separately, zero tracing range can be set
- RS-232 communication interface, multi communication protocol
- Digital load cell SN checking, overload record checking function
- Calibration switch code
- Input password before calibration and adjusting
- Automatic and manual corner-difference adjustment
- Random charging by indicator
- Encryption function is available while load cell and indicator is communicating
- Equipped with EMC protection

TECHNICAL PARAMETERS

- Digital load cell interface : RS-485, max transmission distance \leq 75m
- Transmission speed rate : 19200 bps
- Digital load cell power supply : DC 12V/750mA
- Digital load cell connection quantity : 1 ~ 4 pcs
- Digital load cell communication protocol : MK-SLB-D protocol
- Display : 6 LED digital tube with 1.2 inch red light, 7 state instruction
- Serial communication interface : RS-232, 600 ~ 19200 bps optional
- Indicator power supply : AC : Switch power supply 110V ~ 200V/AC, 50Hz
- Operating temperature : 0°C ~ 40°C Humidity : \leq 85% (RH)
- Storage temperature : 10°C ~ 60°C Storage Humidity : \leq 95% (RH)

SPECIFICATIONS

Specifications:

Platform size (mm)	Capacity (kg)	Readability (kg)
1000 x 1000	1000	0.2
1200 x 1200	2000	0.5
1500 x 1500	2000	0.5
1500 x 1500	3000	1
1500 x 1500	5000	1
1500 x 2000	3000	1
1500 x 2000	5000	1
2000 x 2000	3000	1
2000 x 2000	5000	2
2000 x 3000	3000	1
2000 x 3000	5000	2

MK-Di02 Load bar

Floor scale MK-Di02 gives you the tools to improve profitability and efficiency in many weight-based processes across the Farm.

