

Indicator SGW-3015S

The GSC SGW-3015S is built tough with an all steel enclosure, for extra long life in industrial environment. A simple six button front panel and bright red LED Display (3cm high) Provide easy operation and Monitoring. The standard internal rechargeable battery allows the indicator to be used anywhere or to keep you weighing even during power outages.



APPLICATIONS

- Straight weighing, Truck scales, Shipping and Receiving, Panel mounting

OPTIONS

- SGW-3015S with RS-232, SGW-3015TS with RS-232 and calendar

FEATURES

- Six button operation
- Full front-panel digital calibration set up capacity, and accuracy
- AC/ DC 90-250V/ 50-60Hz adapter (supplied)
- Internal Rechargeable battery (6V/ 4.5Ah)
- Drive up to 8each, 350 OHM load cells
- Selectable display accuracy 1/3,000, 1/5,000 1/6,000 and 1/10,000 1/12,000 and 1/15,000
- Weight unit : kg, lb, kg/lb conversion, Guatemala lb (1 lb= 460g), kg/ Guatemala lb
- Super -bright red LED display 3cm high, 5 digit
- Universal mounting stand
- Selectable capacity from 600 g to 100 tons (or 2 lb to 999.99 lb)
- Coated-paint steel enclosure